



# KEY FEATURES

- Manual zoom (PO version available)
- Continuously variable CCT from 2.800 to 6.500 K (CRI avg. > 94)
- Electronic 16 bit dimming with 3 selectable curves (Exponential, Logarithmic, Linear)
- Fan setting with 4 different options (Low, Auto, Studio or DMX regulated)
- Guaranteed flicker-free



#### SPECIFICATIONS

- CCT proportional control from 2.800 to 6.500 K  $\,$
- Fresnel lens (diameter: 200 mm / 7.87 in)
- Manual zoom range from 14° to 81° (PO zoom available)
- Electronic 16 bit dimming with 3 selectable curves (exponential, logarithmic,
- Synchronized, random or pulse electronic strobe
- Flicker-free operation with LEDs frequency controlled via DMX from 600 to 19.000 Hz
- Fan setting with 4 different options (low, auto, studio or DMX regulated)
- IP rating: 20
- CE approved

#### LIGHT SOURCE

- Variable white LEDs module (CRI 92 at 3.200 K CRI 95 at 5.600 K)
- Average LED lifetime: a minimum of 80% of the initial luminous flux will be maintained after approx. 50.000 hours of usage (50.000 LM80)

#### PHYSICAL SIZE

- Length: 409 mm (16.10 in) - Width: 317 mm (12.48 in)
- Height: 315 mm (12.40 in)
- Weight: 13.5 Kg (29.76 lbs)

## CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512A
- DMX channels: 5 / 2 / 1
- Setting, addressing, testing and measurements via LEDs display
- RDM (Remote Device Management)

# ELECTRICAL **SPECIFICATIONS** AND CONNECTIONS

- AC power: 80-264 V, auto-sensing, 50/60 Hz Max power consumption: 245 W
- Power consumption: 1.13 A at 230 V, 2.17 A at 115 V  $\cos \varphi$  0.94 min.
- In and Out PowerCon TRUE connectors
- DMX data in/out: 5 pin locking XLR

#### **ACCESSORIES**


- 8-leaf barndoor
- Color frame holder


### AVAII ABI F VFRSIONS


- Pole operated zoom and yoke (F050G010P)



### DRAWING SIZE







## DMX CHARTS \_\_\_\_\_

5 channels		
1	master dimmer	
2	dimmer fine	
3	white tone	
4	strobe	
5	special function	

2 channels		
1	master dimmer	
2	white tone	

1 channel		
1	master dimmer (color temperature settable by display)	

### PHOTOMETRIC DATA -

The Otello Photometric Data may be downloaded from  ${\it www.coemar.com}.$ 

# ACCESSORIES \_\_\_\_\_

Code	Description
TBC	8-leaf barndoor
TBC	Color frame holder