



# KEY FEATURES

- Light source: 100 W Daylight COB LEDs
- CRI 90
- 16° 77° proportional zoom (with Fresnel lens)
- 10° 85° proportional zoom (with PC lens)
- Smooth 16 bit dimmer
- Guaranteed flicker-free operation (DMX controlled PWM frequency)
- The fan setting allows three options: low, auto and DMX regulated



#### **SPECIFICATIONS**

- Fixed white CCT: 5.600 K
- Fresnel or PC lenses (diameter 120 mm /  $4.7 \, \mathrm{in}$ )
- Zoom range from 16° to 77° (with Fresnel lens)
- Zoom range from 10° to 85° (with PC lens)
- Electronic 16 bit dimming with 3 selectable curves (exponential, logarithmic and linear)
- Synchronized, random or pulse electronic strobe
- Flicker-free operation with LEDs frequency controlled via DMX from 600 to 19.000 Hz
- Fan setting with 3 different options (low, auto, DMX regulated)
- IP rating: 20
- CE approved

### LIGHT SOURCE

- Daylight COB LED (CRI 90)
- Average LED lifetime: a minimum of 80% of the initial luminous flux will be maintained after approx. 50.000 hours of usage (50.000 LM80)

### PHYSICAL SIZE

- Length: 308 mm (12.13 in)
- Width: 251 mm (9.88 in) - Height: 185 mm (7.28 in)
- Height with bracket: 288 mm (11.34 in)
- Weight: 5.5 Kg (12.13 lbs)

## CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512A
- DMX channels: 5 / 1
- Setting, addressing, testing and measurements via LEDs display
- RDM (Remote Device Management)

## ELECTRICAL **SPECIFICATIONS** AND CONNECTIONS


- AC power: 90-264 V, auto-sensing, 50/60 Hz Max power consumption: 100 W
- Power consumption: 0.46 A at 230 V, 0.92 A at 115 V  $\cos\phi$  0.95
- In and Out PowerCon connectors
- DMX data in/out: 5 pin locking XLR


#### **ACCESSORIES**


- 4-leaf barndoor



## DRAWING SIZE -







## DMX CHARTS -

5 channels				
1	master dimmer			
2	spare channel			
3	dimmer fine			
4	strobe			
5	special function			

1 channel				
1	master dimmer			

## PHOTOMETRIC DATA -

The Risalto Photometric Data may be downloaded from www.coemar.com.

# ACCESSORIES -

Code	Description
ACO4201	4-leaf barndoor